

STEEL FIX C-STAHL

CP450 STEELFIX carbon steel press-fit-adapter with male thread 89x3"

54702K14

Areas of application



?Press-adapter with male thread conforming to EN 10226-1 made of carbon steel coated with a zinc layer, incl. EPDM sealing elements, d15-54 "leak before pressed"

Press contour: M

Specifications

Article information

| | |
|---------------|----------------------------|
| port 1 | Pressmuffe |
| port 2 | Außengewinde konisch (NPT) |
| execution | 1-part |
| design | gerade |
| press contour | M |

Technical properties

| | |
|------------------------------------|--------|
| maximum working pressure at 20 ° C | 16 bar |
|------------------------------------|--------|

Product information

| | |
|---------------------|--|
| VPE1 | 2,00 SA1 |
| VPE2 | 24,00 KT1 |
| weight | 1,160 KGM |
| text | STEELFIX carbon steel press-fit-adapter with male thread |
| INTRNR | 73079980 |
| main material group | STEELFIX |
| material group | C-STAHL pressfittings |
| code | CP450 |



| Art. No | label | d2 Inches | d1 mm | L1 mm | L2 mm | z1 mm | slw2 mm |
|----------|-------|-------------|-------|-------|-------|-------|---------|
| 54702K14 | 89x3" | 3 Zoll (80) | 89 | 90 | 41,5 | 29 | 95 |