

# KELOX

## KMP450X KELOX-PROTEC CLIX adapter with male thread 32x3/4"

730202F04

### Areas of application



Push-in adapter with male thread, made of dezincification-resistant (DZR) brass, incl. push-on sleeve made of transparent polyamide with insertion click noise, as well as haptic and optical insertion indicator, O-rings, withdrawal barriers and protector ring as an insertion locking device

### Approvals:



KE KELIT GmbH

A 4020 Linz, Ignaz-Mayer-Straße 17, Austria, Europe

PHONE +43 (0) 50 779 E-MAIL [office@kekelit.com](mailto:office@kekelit.com)

[www.kekelit.com](http://www.kekelit.com)

# Specifications

## Article information

|           |   |
|-----------|---|
| port 1    | Plug-in                                     |
| port 2    | Female thread cylindrical BSPT-Rp (ISO 7-1) |
| execution | Miscellaneous                               |
| design    | Straight                                    |

## Technical properties

|                                    |        |
|------------------------------------|--------|
| maximum working pressure at 20 ° C | 10 bar |
|------------------------------------|--------|

## Product information

|                     |  |
|---------------------|--|
| VPE1                | 10,00 SA1                                  |
| VPE2                | 60,00 KT1                                  |
| weight              | 0,136 KGM                                  |
| text                | KELOX-PROTEC CLIX adapter with male thread |
| INTRNR              | 74122000                                   |
| main material group | KELOX                                      |
| material group      | KELOX-PROtec pushfittings                  |
| code                | KMP450X                                    |



| Art. No   | label   | d2        | d1 mm | L1 mm | z1 mm | z2 mm | slw1 mm |
|-----------|---------|-----------|-------|-------|-------|-------|---------|
| 730202F04 | 32x3/4" | 3/4" (20) | 32    | 39    | 4     | 39    | 38      |