


KELOX

KWP410X KELOX-PROTEC CLIX PPSU coupling 20/20

730600DD0

Areas of application



?Push-in coupling equal or reduced, made of PPSU, incl. push-on sleeve made of transparent polyamide, with insertion click noise, as well as haptic and optical insertion indicator, O-rings, withdrawal barriers and a protector ring as an insertion locking device

Approvals:



KE KELIT GmbH

A 4020 Linz, Ignaz-Mayer-Straße 17, Austria, Europe

PHONE +43 (0) 50 779 E-MAIL office@kekelit.com

www.kekelit.com

Specifications

Article information


port 1	Plug-in
port 2	Plug-in
execution	Miscellaneous
design	straight

Technical properties

maximum working pressure at 20 ° C	10 bar
------------------------------------	--------

Product information

VPE1	10,00 SA1
VPE2	140,00 KT1
weight	0,028 KGM
text	KELOX-PROTEC CLIX PPSU coupling
INTRNR	39174000
main material group	KELOX
material group	KELOX-PROtec-PPSU pushfittings
code	KWP410X



Art. No	label	d1 mm	d2 mm	L1 mm	L2 mm	z1 mm	z2 mm
730600DD0	20/20	20	20	37,5	37,5	5,5	5,5