

STEEL FIX C-STAHl

CP421 STEELFIX carbon steel press-fit 90°
elbow male/female 42

54616GG0

Areas of application



Press-elbow 90°, f/m, made of carbon steel coated with a zinc layer, incl. EPDM sealing components, d15-54 "leak before pressed"

Press contour: M

Specifications

Article information

| | |
|---------------|-----------------|
| port 1 | Pressmuffe |
| port 2 | Zapfen/Rohrende |
| execution | 1-part |
| design | Bogen |
| angle | 90 ° |
| press contour | M |

Technical properties

| | |
|------------------------------------|--------|
| maximum working pressure at 20 ° C | 16 bar |
|------------------------------------|--------|

Product information

| | |
|---------------------|---|
| VPE1 | 2,00 SA1 |
| VPE2 | 8,00 KT1 |
| VPE3 | 200,00 DDP |
| weight | 0,329 KGM |
| text | STEELFIX carbon steel press-fit 90° elbow male/female |
| INTRNR | 73079980 |
| main material group | STEELFIX |
| material group | C-STAHL pressfittings |
| code | CP421 |



| Art. No | label | d1 mm | d2 mm | L1 mm | L2 mm | z1 mm | z2 mm |
|----------|-------|-------|-------|-------|-------|-------|-------|
| 54616GG0 | 42 | 42 | 42 | 86 | 92,5 | 56 | 62,5 |