

# STEEL FIX C-STAHl

CP450 STEELFIX carbon steel press-fit-adapter with male thread 15x1/2"

54702B02

## Areas of application



?Press-adapter with male thread conforming to EN 10226-1 made of carbon steel coated with a zinc layer, incl. EPDM sealing elements, d15-54 "leak before pressed"

Press contour: M

# Specifications

## Article information

|               |                            |
|---------------|----------------------------|
| port 1        | Pressmuffe                 |
| port 2        | Außengewinde konisch (NPT) |
| execution     | 1-part                     |
| design        | gerade                     |
| press contour | M                          |

## Technical properties

|                                    |        |
|------------------------------------|--------|
| maximum working pressure at 20 ° C | 16 bar |
|------------------------------------|--------|

## Product information

|                     |  |
|---------------------|--|
| VPE1                | 10,00 SA1  |
| VPE2                | 200,00 KT1   |
| VPE3                | 5000,00 DDP  |
| weight              | 0,047 KGM  |
| text                | STEELFIX carbon steel press-fit-adapter with male thread |
| INTRNR              | 73079980   |
| main material group | STEELFIX   |
| material group      | C-STAHL pressfittings                                    |
| code                | CP450  |



| Art. No  | label   | d2 Inches | d1 mm | L1 mm | L2 mm | z1 mm | slw2 mm |
|----------|---------|-----------|-------|-------|-------|-------|---------|
| 54702B02 | 15x1/2" | 1/2" (15) | 15    | 22    | 17    | 4     | 24      |