

KELOX_{FB}

KMP590Z KELOX-PROTEC FB stainless steel push fitting manifold, 10bar 2 L: 225mm

73173020

Areas of application



?Stainless steel flow and return flow bar with pluggable heating circuit outlets, with bleeding and emptying at the manifold end, connections with screwed-in 1" flat-sealing cap nut. Return flow valve bonnets suitable for KM596 KELOX thermal motor, flow shut-off valve, incl. sound-insulated steel consoles

Application area: tmax. 70°C/10 bar

ATTENTION: WITHOUT KMP552 PROTEC quick-push coupling!

Specifications

Article information

| | |
|-------------------|---|
| extendible | 1 |
|-------------------|---|

Product information

| | |
|-------------|----------|
| VPE1 | 1,00 KT1 |
|-------------|----------|


| | |
|-------------|------------|
| VPE2 | 119,00 PAL |
|-------------|------------|

| | |
|---------------|-----------|
| weight | 2,130 KGM |
|---------------|-----------|

| | |
|-------------|--|
| text | KELOX-PROTEC FB stainless steel push fitting manifold, 10bar |
|-------------|--|

| | |
|---------------|----------|
| INTRNR | 84818099 |
|---------------|----------|

| | |
|-------------|---------|
| code | KMP590Z |
|-------------|---------|



| Art. No | label | t mm | t mm | h mm |
|----------|------------|------|------|------|
| 73173020 | 2 L: 225mm | 80 | 225 | 305 |