


# KELEN

## KE35-LX4 KELEN PP-RCT LX-SENSO reducer tee 25/20/25

2572041

### Areas of application



KELEN PP-RCT SENSO Polyfusion welding fitting for connecting pipes with fittings made of the same material (no reduction of internal diameter) and a factory-installed 4mm soft-foam insulation, can be located electronically, outer layer consisting of woven tape fabric and viscoplastic polymer alloy

## Approvals:



# Specifications

## Article information

port 1	Kunststoffschweißmuffe
port 2	Kunststoffschweißmuffe
port 3	Kunststoffschweißmuffe
execution	T-Stück
angle	90 °

## Technical properties

maximum working pressure at 20 ° C	20 bar
isolation thickness	4 mm

## Product information

VPE1	10,00 SA1
VPE2	50,00 KT1
VPE3	300,00 KT2
VPE4	4800,00 PAL
weight	0,049 KGM
text	KELEN PP-RCT LX-SENSO reducer tee
INTRNR	39174000
main material group	KELEN
material group	KELEN-LX fittings
code	KE35-LX4



Art. No	label	d1 mm	d2 mm	d3 mm	L1 mm	L2 mm	L3 mm	z1 mm	z2 mm	z3 mm
2572041	25/20/25	25	20	25	36	31	36	16	16	16