


# KELEN

## KE35-LX4 KELEN PP-RCT LX-SENSO reducer tee 32/25/32

2573041

### Areas of application



KELEN PP-RCT SENSO Polyfusion welding fitting for connecting pipes with fittings made of the same material (no reduction of internal diameter) and a factory-installed 4mm soft-foam insulation, can be located electronically, outer layer consisting of woven tape fabric and viscoplastic polymer alloy

## Approvals:



# Specifications

## Article information

port 1	Kunststoffschweißmuffe
port 2	Kunststoffschweißmuffe
port 3	Kunststoffschweißmuffe
execution	T-Stück
angle	90 °

## Technical properties

maximum working pressure at 20 ° C	20 bar
isolation thickness	4 mm

## Product information

VPE1	5,00 SA1
VPE2	25,00 KT1
VPE3	150,00 KT2
VPE4	2400,00 PAL
weight	0,096 KGM
text	KELEN PP-RCT LX-SENSO reducer tee
INTRNR	39174000
main material group	KELEN
material group	KELEN-LX fittings
code	KE35-LX4



Art. No	label	d1 mm	d2 mm	d3 mm	L1 mm	L2 mm	L3 mm	z1 mm	z2 mm	z3 mm
2573041	32/25/32	32	25	32	42	38	42	17	16	17