

# KELOX<sub>FB</sub>

KMP590E KELOX-PROTEC FB stainless steel push fitting manifold 13 L: 775mm

73171130

## Areas of application



?Stainless steel flow and return flow bar with pluggable heating circuit outlets, with bleeding and emptying at the manifold end, connections with screwed-in 1" flat-sealing cap nut. Return flow valve bonnets suitable for KM596 KELOX thermal motor, flow water meter of 0.5-5.0 l/min adjustable, incl. sound-insulated steel consoles

Application area: tmax. 70°C/6 bar

ATTENTION: WITHOUT KMP552 PROTEC quick-push coupling!

# Specifications

## Article information

|                   |   |
|-------------------|---|
| <b>extendible</b> | 1 |
|-------------------|---|

## Product information

|             |          |
|-------------|----------|
| <b>VPE1</b> | 1,00 KT1 |
|-------------|----------|

|             |           |
|-------------|-----------|
| <b>VPE2</b> | 49,00 PAL |
|-------------|-----------|

|               |           |
|---------------|-----------|
| <b>weight</b> | 6,546 KGM |
|---------------|-----------|

|             |   |
|-------------|---|
| <b>text</b> | KELOX-PROTEC FB stainless steel push fitting manifold |
|-------------|---|

|               |          |
|---------------|----------|
| <b>INTRNR</b> | 84818099 |
|---------------|----------|

|             |         |
|-------------|---------|
| <b>code</b> | KMP590E |
|-------------|---------|



| Art. No  | label       | t mm | t mm | h mm |
|----------|-------------|------|------|------|
| 73171130 | 13 L: 775mm | 70   | 775  | 335  |