

KELOX

KMP450X KELOX-PROTEC CLIX adapter with male thread 25x1"

730202E05

Areas of application



Push-in adapter with male thread, made of dezincification-resistant (DZR) brass, incl. push-on sleeve made of transparent polyamide with insertion click noise, as well as haptic and optical insertion indicator, O-rings, withdrawal barriers and protector ring as an insertion locking device

Approvals:



Specifications

Article information

| | |
|-----------|---|
| port 1 | Plug-in |
| port 2 | Female thread cylindrical BSPT-Rp (ISO 7-1) |
| execution | Miscellaneous |
| design | Straight |

Technical properties

| | |
|------------------------------------|--------|
| maximum working pressure at 20 ° C | 10 bar |
|------------------------------------|--------|

Product information

| | |
|---------------------|--|
| VPE1 | 10,00 SA1 |
| VPE2 | 80,00 KT1 |
| weight | 0,168 KGM |
| text | KELOX-PROTEC CLIX adapter with male thread |
| INTRNR | 74122000 |
| main material group | KELOX |
| material group | KELOX-PROtec pushfittings |
| code | KMP450X |



| Art. No | label | d2 | d1 mm | L1 mm | z1 mm | z2 mm | slw1 mm |
|-----------|-------|----|-------|-------|-------|-------|---------|
| 730202E05 | 25x1" | 1" | 25 | 40 | 4 | 39 | 30 |