

# KELOX

## KMU100 KELOX-ULTRAX multilayer pipe 16x2

7021602

### Areas of application



?KELOX-ULTRAX multilayer pipe for CLIMATEFIX based on ÖNORM EN ISO 21003, an oxygen- and water vapour diffusion-tight 5-layer PE-RT/Al/PE-RT composite pipe

Application range: 60°C - tmax 70°C/10 bar

Colour: white/transparent

Supplied in coils

ATTENTION - This is NOT a drinking water and radiator connection pipe!

## Approvals:



**KE KELIT GmbH**

A 4020 Linz, Ignaz-Mayer-Straße 17, Austria, Europe

**PHONE** +43 (0) 50 779 **E-MAIL** [office@kekelit.com](mailto:office@kekelit.com)

[www.kekelit.com](http://www.kekelit.com)

# Specifications

## Article information

color White

flexible 1

isolation 0

## Technical properties

maximum working pressure at 20 ° C 10

pipe weight 0.11

pipe contents 0,113 l/m

lambda pipe 0.45

wall rawness 0,007 mm

expansion coefficient 0,025 mm/(m.K)

## Product information

VPE1 200 ROL

VPE2 2400 PAL

L 200 m

weight 0,11 KGM

text KELOX-ULTRAX multilayer pipe

INTRNR 39173900

main material group KELOX

material group KELOX-ULTRAX pipes

code KMU100



Art. No	label	d1 mm	pipe contents l/m	s
7021602	16x2	16	0,113	2



**KE KELIT GmbH**

A 4020 Linz, Ignaz-Mayer-Straße 17, Austria, Europe

**PHONE** +43 (0) 50 779 **E-MAIL** [office@kekelit.com](mailto:office@kekelit.com)

[www.kekelit.com](http://www.kekelit.com)