

KELOX

KMU440 KELOX-ULTRAX tee 63/50/63

71110IH1

Areas of application



Press tee equal or reduced, made of non-porous metallized brass, incl. support sleeves with O-rings and steel or stainless steel press-fit sleeves, "leak before pressed"

Approvals:



Specifications

Article information

| | |
|---------------|-----------------|
| port 1 | Pressing socket |
| port 2 | Pressing socket |
| port 3 | Pressing socket |
| execution | Tee piece |
| angle | 90 |
| press contour | U |

Technical properties

| | |
|------------------------------------|--------|
| maximum working pressure at 20 ° C | 16 bar |
|------------------------------------|--------|

Product information

| | |
|---------------------|-----------------------------|
| VPE1 | 1 SA1 |
| VPE2 | 2 KT1 |
| weight | 1,435 KGM |
| text | KELOX-ULTRAX tee |
| INTRNR | 74122000 |
| main material group | KELOX |
| material group | KELOX-ULTRAX metal fittings |
| code | KMU440 |



| Art. No | label | d1 | d2 mm | d3 | L1 mm | L2 mm | L3 mm | z1 mm | z2 mm | z3 mm |
|----------|----------|----|-------|----|-------|-------|-------|-------|-------|-------|
| 71110IHI | 63/50/63 | 63 | 50 | 63 | 104 | 87 | 104 | 41 | 46 | 41 |