

# KELOX

## KMU455 KELOX-ULTRAX union with female thread 16x1/2"

71203B02

### Areas of application



?Press-fit union with female thread for connection to fittings and devices such as filters, manifolds, pumps,..... made of non-porous metallised brass, incl. support sleeves with O-rings and stainless steel pressing sleeves, "leak before pressed", flat-sealing including seal

### Approvals:



# Specifications

## Article information

|               |                 |
|---------------|-----------------|
| port 1        | Pressing socket |
| port 2        | Union nut       |
| execution     | 2-part          |
| design        | Straight        |
| press contour | U               |

## Technical properties

|                                    |        |
|------------------------------------|--------|
| maximum working pressure at 20 ° C | 10 bar |
|------------------------------------|--------|

## Product information

|                     |                                       |
|---------------------|---------------------------------------|
| VPE1                | 10,00 SA1                             |
| VPE2                | 200,00 KT1                            |
| weight              | 0,058 KGM                             |
| text                | KELOX-ULTRAX union with female thread |
| INTRNR              | 74122000                              |
| main material group | KELOX                                 |
| material group      | KELOX-ULTRAX metal fittings           |
| code                | KMU455                                |



| Art. No  | label   | d2 Inches | d1 mm | L1 mm | L2 mm | z1 mm | slw2 mm |
|----------|---------|-----------|-------|-------|-------|-------|---------|
| 71203B02 | 16x1/2" | 1/2" (15) | 16    | 38,5  | 8,5   | 16    | 24      |