

# KETRIX

## TRI08 KETRIX industrial pipe - PN16 63x8.6

55008I00

### Areas of application



KETRIX industrial piping system based on ÖNORM EN ISO 15874 made of polyolefin blend (POB) for COOLING WATER, COLD and COMPRESSED AIR up to 10 bar

Area of application: 20°C/16 bar, from -30°C to +40°C/10 bar

Colour: burgundy with 3 co-extruded white longitudinal stripes

Length: 4m

# Specifications

## Article information

port 1	Pipe end
port 2	Pipe end
color	Burgundy

## Technical properties

pipe weight	1.41 kg/m
pipe contents	1.65 l/m
PN	PN 16
lambda pipe	0.24 W/(m.K)
wall rawness	0.007
expansion coefficient	0.14 mm/(m.K)

## Product information

DIM2	45,8
VPE1	12 BND
L	4 m
weight	1,41 KGM
text	KETRIX industrial pipe - PN16
INTRNR	39172290
main material group	KETRIX
material group	KETRIX pipes
code	TRI08



Art. No	label	d1	pipe contents l/m	s
55008100	63x8.6	63	1.65	8.6



**KE KELIT GmbH**

A 4020 Linz, Ignaz-Mayer-Straße 17, Austria, Europe

**PHONE** +43 (0) 50 779 **E-MAIL** [office@kekelit.com](mailto:office@kekelit.com)

[www.kekelit.com](http://www.kekelit.com)