


# KELEN

## KE08-LX9 KELEN PP-RCT LX-SENSO pipe - PN16 20x2.8

1620091

### Areas of application



KELEN PP-RCT SENSO drinking water pipe system conforming to ÖNORM EN ISO 15874 made of polypropylene (PP-RCT) with factory-installed 9mm soft-foam insulation, can be located electronically; outer layer consisting of woven tape fabric and viscoplastic polymer alloy

Application area: 20°C/16 bar - 70°C/10 bar

Length: 4m

## Approvals:



# Specifications

## Technical properties

isolation thickness	9 mm
pipe weight	0,22 kg/m
pipe contents	0,16 l/m
thermal conductivity	0,039 W/(m.K)
diameter inner tube	20 mm

## Product information

DIM2	14,4
VPE1	60,00 BND
VPE2	2100,00 HOB
L	4 m
weight	0,204 KGM
text	KELEN PP-RCT LX-SENSO pipe - PN16
INTRNR	39172290
main material group	KELEN
material group	KELEN-LX pipes
code	KE08-LX9



Art. No	label	d mm	pipe contents l/m
1620091	20x2.8	14,4	0,16



**KE KELIT GmbH**

A 4020 Linz, Ignaz-Mayer-Straße 17, Austria, Europe

**PHONE** +43 (0) 50 779 **E-MAIL** [office@kekelit.com](mailto:office@kekelit.com)

[www.kekelit.com](http://www.kekelit.com)