

STEEL FIX C-STAHl

CP440 C-Steel press-tee 18/22/18

54630CDC

Areas of application



Press-fit tee equal or reduced made of carbon steel coated with a zinc layer, incl. EPDM sealing components, d15-54 "leak before pressed"

Press contour: M

Specifications

Article information

| | |
|---------------|------------|
| port 1 | Pressmuffe |
| port 2 | Pressmuffe |
| port 3 | Pressmuffe |
| execution | T-Stück |
| press contour | M |

Technical properties

| | |
|------------------------------------|--------|
| maximum working pressure at 20 ° C | 16 bar |
|------------------------------------|--------|

Product information

| | |
|---------------------|-----------------------|
| VPE1 | 10 SA1 |
| VPE2 | 50 KT1 |
| VPE3 | 1250 DDP |
| weight | 0,091 KGM |
| text | C-Steel press-tee |
| INTRNR | 73079980 |
| main material group | STEELFIX |
| material group | C-STAHL pressfittings |
| code | CP440 |



| Art. No | label | d1 mm | d2 mm | d3 mm | L1 mm | L2 mm | L3 mm | z1 mm | z2 mm | z3 mm |
|---------|----------|-------|-------|-------|-------|-------|-------|-------|-------|-------|
| 54630CD | 18/22/18 | 18 | 22 | 18 | 37 | 47 | 37 | 17 | 26 | 17 |