

# KMU121K KELOX-ULTRAX FB Velcro tube 16x2

7001613

## Areas of application



?KELOX-ULTRAX FB Velcro tube conforming to ÖNORM EN ISO 21003; oxygen- and water vapour-tight

5-layer multilayer pipe made of PE-RT/Al/ PE-RT; incl. coiled Velcro strip for fixing directly on the KM636 and KM636K KELOX FB Velcro panel and foil without any additional fixing

Classification of operating conditions according to ÖNORM EN ISO 21003

Underfloor heating - Class 4: 60°C - tmax 70°C/10 bar

Colour: blue/transparent

Rolled product

## Approvals:



KE KELIT GmbH

A 4020 Linz, Ignaz-Mayer-Straße 17, Austria, Europe

PHONE +43 (0) 50 779 E-MAIL [office@kekelit.com](mailto:office@kekelit.com)

[www.kekelit.com](http://www.kekelit.com)

# Specifications

## Article information

**color** Blue

**flexible** 1

## Technical properties

**maximum working pressure at 20 ° C** 10 bar

**pipe weight** 0,11 kg/m

**pipe contents** 0,113 l/m

**lambda pipe** 0,45 W/(m.K)

**wall rawness** 0,007 mm

**expansion coefficient** 0,025 mm/(m.K)

## Product information

**VPE1** 300,00 ROL

**VPE2** 2700,00 PAL

**L** 300 m

**weight** 0,110 KGM

**text** KELOX-ULTRAX FB Velcro tube

**INTRNR** 39173900

**code** KMU121K



Art. No	label	d1 mm	pipe contents l/m	s mm
7001613	16x2	16	0,113	2



**KE KELIT GmbH**

A 4020 Linz, Ignaz-Mayer-Straße 17, Austria, Europe

**PHONE** +43 (0) 50 779 **E-MAIL** [office@kekelit.com](mailto:office@kekelit.com)

[www.kekelit.com](http://www.kekelit.com)