


KELOX_{FB}

KM590E KELOX FB manifold 2 L: 175mm

7902500

Areas of application



?Feed and return flow bar with heating circuit outlets 3/4" euro cone with male thread, with bleeding at the highest point and draining, manifold ends closed, connections with pre-formed union nut 1" flat-sealing, manifold ends with 1" male thread, for screwing together individual manifold bars without additional connectors, on the feed line, pre-settable double-spindle valve, top parts to fit KM596 KELOX thermal motor, on the return flow water flow meter (0.5-2.5 l/min), non-porous metallised brass, incl. labelled plates for each heating circuit and sound-insulated metal consoles (1 circuit) without drain outlet, bleeding and metal console

Application area: tmax. 80°C/6 bar

ATTENTION: WITHOUT KM220 Euro thread fitting!

Specifications

Article information

extendible	1
-------------------	---

Product information


VPE1	1,00 KT1
-------------	----------

weight	1,884 KGM
---------------	-----------

text	KELOX FB manifold
-------------	-------------------

INTRNR	84818099
---------------	----------

code	KM590E
-------------	--------



Art. No	label	t mm	t mm	h mm
7902500	2 L: 175mm	80	176	305



KE KELIT GmbH

A 4020 Linz, Ignaz-Mayer-Straße 17, Austria, Europe

PHONE +43 (0) 50 779 **E-MAIL** office@kekelit.com

www.kekelit.com