

KELOX

KMP489 KELOX-PROTEC - STEELFIX adapter 20/22

73272DD0

Areas of application



?Press/push-in adapter, straight, from Steelfix, Copperfix pipe size to KELOX-PROTEC - push-in sleeve made of red brass, incl. support sleeves, O-rings, withdrawal barriers and a protector ring as an insertion locking device

ATTENTION! Connection to pipe end only suitable as a compression fitting or press-fit connection!

Approvals:



Specifications

Article information

| | |
|--------|-----------------|
| port 1 | Plug-in |
| port 2 | Zapfen/Rohrende |
| design | Straight |

Technical properties

| | |
|------------------------------------|--------|
| maximum working pressure at 20 ° C | 10 bar |
|------------------------------------|--------|

Product information

| | |
|---------------------|---------------------------------|
| VPE1 | 10,00 SA1 |
| VPE2 | 100,00 KT1 |
| weight | 0,068 KGM |
| text | KELOX-PROTEC - STEELFIX adapter |
| INTRNR | 74122000 |
| main material group | KELOX |
| material group | KELOX-PROtec pushfittings |
| code | KMP489 |



| Art. No | label | d1 mm | d2 mm | L1 mm | L2 mm | z1 mm |
|----------|-------|-------|-------|-------|-------|-------|
| 73272DD0 | 20/22 | 20 | 22 | 47 | 21 | 16 |