

# KELOX<sub>FB</sub>

## KMP590E KELOX-PROTEC FB stainless steel push fitting manifold Feed line nipple

731710VL

### Areas of application



?Stainless steel flow and return flow bar with pluggable heating circuit outlets, with bleeding and emptying at the manifold end, connections with screwed-in 1" flat-sealing cap nut. Return flow valve bonnets suitable for KM596 KELOX thermal motor, flow water meter of 0.5-5.0 l/min adjustable, incl. sound-insulated steel consoles

Application area: tmax. 70°C/6 bar

ATTENTION: WITHOUT KMP552 PROTEC quick-push coupling!

# Specifications

## Product information

<b>VPE1</b>	1,00 STK
<b>VPE2</b>	10,00 SA1
<b>weight</b>	0,070 KGM
<b>text</b>	KELOX-PROTEC FB stainless steel push fitting manifold
<b>INTRNR</b>	84818099
<b>code</b>	KMP590E



**KE KELIT GmbH**

A 4020 Linz, Ignaz-Mayer-Straße 17, Austria, Europe

**PHONE** +43 (0) 50 779 **E-MAIL** office@kekelit.com

[www.kekelit.com](http://www.kekelit.com)



Art. No

label

731710VL

Feed line nipple