

KELOX

KM100 ?KELOX multilayer pipe 16x2/200

7521160E

Felhasználási terület



?KELOX multilayer pipe conforming to ÖNORM EN ISO 21003, oxygen-and water vapour diffusion-tight 5-layer PE-RT/Al/PE-RT composite pipe

Operating conditions classified acc. to ÖNORM EN ISO 21003

Sanitary application - Class 2: 70°C - tmax 80°C/10 bar

Radiator connection - Class 5: 80°C - tmax 90°C/10 bar

Colour: white/transparent

Supplied in coils

Engedélyek:



Specifikáció

Termékinformációk

Farbe White

Flexibilis 1

Műszaki tulajdonságok

Max. üzemi nyomás 20°C-nál 10 bar

Cs? tömege 0.11 kg/m

Cs? bels? térfogata 0.113 l/m

Cs? Lambda 0,45 W/(m.K)

Cs?fal érdessége 0.007 mm

Tágulási együttható 0.025 mm/(m.K)

Termékinformációk

VPE1 200,00 ROL

VPE2 2000,00 PAL

L 200 m

Tömeg 0,111 KGM

Szöveg ?KELOX multilayer pipe

BELS? 39173900

Áruf?csoport KELOX

Áruf?csoport KELOX pipes

Kód KM100





KE KELIT GmbH

A 4020 Linz, Ignaz-Mayer-Straße 17, Austria, Europe

PHONE +43 (0) 50 779 **E-MAIL** office@kekelit.com

www.kekelit.com